



PERCEUSES FIXES ET PNEUMATIQUES PORTATIVES BENCH AND PEDESTAL DRILLS / PORTABLE PNEUMATIC DRILLS



- Classe H Industrie
- Capacité maximale de serrage de 6.5 à 26 mm
- Emmanchements coniques et taraudés
- Habillage en acier massif


- Class H Industry
- Maxima drilling capacity from 6.5 to 26 mm
- Jacobs taper or internal threaded type mountings
- Steel sleeve



BOÎTE / BOX

EMMANCHEMENT CONIQUES TAPER TYPE MOUNTINGS

	JACOBS	mm	mm	JACOBS	JACOBS	JACOBS	D	L	L1	
							mm	mm	mm	g
601 081F	1A	0.3-6.5	0-1/4	J1	T1	K1	30	43	53	125
401 081F		0.3-6.5	0-1/4	J1	T4	K7	32	43	53	140
601 181BF		0.3-8	0-5/16	J2CT	C30	K30	36	51	60	215
601 182F	2A	0.5-10	0-3/8	J2	T2	K2	42.5	59	73	355
601 143BF	33	1.5-13	1/16-1/2	J33	T5	K32	45	65	81	430
601 043F	34-02	0.5-13	0-1/2	J2	T6	K3	51	67	85	595
601 143F	34-33	0.5-13	0-1/2	J33	T6	K3	51	67	85	580
601 243F	34-06	0.5-13	0-1/2	J6	T6	K3	51	67	85	570
601 184F	3A	0.5-16	0-5/8	J3	T6	K3	60	78	100	935
601 145F	36	5-20	3/16-3/4	J3	T6	K3	60	78	100	910
601 085F		1.5-20	1/16-3/4	J4	C20	K4	75	104	130	2190
601 085BF		5-26	3/16-1-1/32	J4	C20	K4	75	104	130	2135



BOÎTE / BOX

EMMANCHEMENT TARAUDÉS INTERNAL THREADED TYPE MOUNTINGS

602 081A	1B-3B-7B	0.3-6.5	0-1/4	3/8-24	5.5	T1	K1	30	43	53	120
602 381A		0.3-6.5	0-1/4	5/16-24	5.5	T1	K1	30	43	53	120
602 081BA		0.3-8	0-5/16	3/8-24	5.5	C30	K30	36	51	60	220
602 181BA		0.3-8	0-5/16	1/2-20	6.5	C30	K30	36	51	60	215
602 042A	31BA-3B	0.5-10	0-3/8	3/8-24	5.5	C30	K30	36	51	60	220
602 142A	31BA-1/2	0.5-10	0-3/8	1/2-20	6.5	C30	K30	36	51	60	215
602 082A	2BA-3/8	0.5-10	0-3/8	3/8-24	5.5	T2	K2	42.5	59	73	365
602 182BA	32BA-1/2	0.5-10	0-3/8	1/2-20	6.5	T5	K32	45	63	76	440
602 043BA	33BA-3/8	1.5-13	1/16-1/2	3/8-24	5.5	T5	K32	45	63	80	440
602 143BA	33BA-1/2	1.5-13	1/16-1/2	1/2-20	6.5	T5	K32	45	63	80	430
602 443BA	33BA-5/8	1.5-13	1/16-1/2	5/8-16	6.5	T5	K32	45	63	80	450
602 043A		0.5-13	0-1/2	1/2-20	6.5	T6	K3	51	67	85	595
602 143A		0.5-13	0-1/2	5/8-16	6.5	T6	K3	51	67	85	590
602 084A	3B-5/8	0.5-16	1/2-5/8	5/8-16	6.5	T6	K3	60	78	100	970
602 045A	36B-5/8	5-20	3/16-3/4	5/8-16	6.5	T6	K3	60	78	100	940
602 145A	36B-3/4	5-20	3/16-3/4	3/4-A6	6.5	T6	K3	60	78	100	930

CLÉS DE RECHANGE P.11 / KEYS P.11

CLÉS DE RECHANGE P.11 / KEYS P.11